

Data Cable Connection Instructions (Type 5)

Connecting a data cable to your computer and phone is a very simple process, as it is simply a matter of plugging in the cable at both ends. Any complexities involved through the use of a data cable will arise when you start to use software, not when connecting the cable.

1. Place the cable into the bottom of the opening tool, and then fully extend the slide. Check that the phone has been inserted into the opening tool the correct way around.



2. Insert the top of the opening tool into position, again checking the position, in particular, the arrow should be pointing towards the bottom of the phone.

Check that the top and bottom parts of the tool have clipped together at all four sections, and that the plastic prongs on either side of the tool (highlighted opposite) are tucked inside the top of the phone's slide.



3. Gently push the slide in the direction of the arrow, taking care not to use excessive force.

The plastic prongs on the opening tool are used to force the slide and phone apart, so check that they have not been forced down by pushing too hard.



4. Continue pushing the top of the opening tool until it reaches the end of its track on the bottom part of the tool.

Check the plastic prongs (highlighted opposite) have been fully submerged inside the slide.



5. The slide has now been dislodged from the phone, so carefully remove the top of the opening tool to expose the phone's circuit board.

If you use too much force, or move the tool too quickly, then the slide will shut again and you will have to go back to step 2.



6. Connect the cable to the phone, making sure that the cable has clipped onto the runners previously used by the slide.

The cable should be flush against the phone, so check the curved side of the cable connector is facing the camera, and the flat side of the cable connector is facing the slide.

Note: Keep the phone sitting in the bottom of the opening tool when reattaching the slide after use.



7. Locate the 9-pin RS-232 serial port on the back of your computer.



8. Insert the cable into the 9-pin RS-232 serial port and then lock the connector into place by turning the two thumb screws.



9. Turn on your mobile phone.
10. Turn on your computer and then run the required software. Suitable software is recommended in the item description page on our web site.
11. Check all the software settings are correct, and read our software tips and trouble-shooting sheet if your software is causing you problems.

Note: Pictures are for reference purposes only. The procedure may differ depending on the model of phone. Always read the text description as well.